


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H02K 1/14, 1/18 // 15/06		A1	(11) International Publication Number: WO 00/69047
			(43) International Publication Date: 16 November 2000 (16.11.00)
(21) International Application Number: PCT/SE00/00923		(74) Agent: AWAPATENT AB; P.O. Box 5117, S-200 71 Malmö (SE).	
(22) International Filing Date: 10 May 2000 (10.05.00)			
(30) Priority Data: 9901745-1 11 May 1999 (11.05.99) SE		(81) Designated States: AE, AG, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, DZ, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(71) Applicant (for all designated States except US): HÖGANÄS AB [SE/SE]; S-263 83 Höganäs (SE).			
(72) Inventors; and (75) Inventors/Applicants (for US only): JACK, Alan, G. [GB/GB]; Milestone House, Allendale Road, Hexham, Northumberland NE46 2NB (GB). MECROW, Barrie [GB/GB]; 50 Haddington Road, Whitley Bay, Tyne and Wear (GB). EVANS, John, Terence [GB/GB]; 11 Polwarth Crescent, Brunton Park, Gosforth, Newcastle upon Tyne NE3 2EE (GB). BURDESS, James, Stonehouse [GB/GB]; 12 Earnshaw Way, Whitley Bay NE25 9UN (GB). FAWCETT, John, Neville [GB/GB]; Paradise House, Embleton, Northumberland NE66 3UX (GB). STEPHENSON, Dawn [GB/GB]; 78 Debdon Gardens, Heaton, Newcastle upon Tyne NE6 5TS (GB). DICKINSON, Phillip, George [GB/GB]; 9 Lincoln Road, Northburn Green, Cramlington, Northumberland NE23 3XT (GB).		Published With international search report.	
(54) Title: STATOR WITH TEETH FORMED FROM A SOFT MAGNETIC POWDER MATERIAL			
(57) Abstract <p>A stator core for an electrical machine comprises an annular yoke and plurality of teeth spaced circumferentially on the annular yoke and extending radially therefrom, the spaces between the teeth defining circumferentially spaced winding slots. The teeth are formed as separate components from a soft magnetic powder material. Each tooth (1; 11) has non-decreasing cross-sectional dimensions in a direction towards a distal tip (3; 13) along a length of the tooth corresponding to a winding slot, and has the same or smaller cross-sectional dimensions along a proximal end (4; 14) of the tooth. Thereby, the tooth (1; 11) may be assembled with a section (5; 15) of the annular yoke and is able to receive a coil (7) before the assembling with the yoke.</p>			
			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

STATOR WITH TEETH FORMED FROM A SOFT MAGNETIC POWDER MATERIAL

Technical Field

The present invention generally is related to electrical machines, especially motors, and more precisely to the structure of the stator assembly thereof.

Background of the invention and the prior art

Electrical machines work by the interaction of magnetic flux and current. At operating limits the magnetic flux is limited by saturation of the soft magnetic material and the current by the temperature resulting from ohmic heating. If more space is provided for conductor to reduce current densities and hence ohmic heating, the magnetic flux is also reduced and vice versa if more soft magnetic material is included the flux is increased but the conductor area is reduced and ohmic heating increased.

In most machines the conductors are contained in slots. It is necessary to semi-close the slots to obtain a smooth torque output and the result is that placing the windings in the slots is a difficult task which results in a rather poor ratio of conductor area to slot area. Ratios in the region of 50% are considered good. This poor ratio is bad for two reasons, firstly space is wasted which could be used for conductor or soft magnetic material and secondly the space in the slot will act as a thermal barrier increasing the temperature for a given ohmic loss.

Summary

An object of this invention is to provide a stator core for an electrical machine which stator core provides a better ratio of conductor area to slot area than stators in the prior art.

This object is achieved in that a stator in accordance with the present invention is characterised by

the features specified in the appended claim 1. Preferred embodiments of that stator are defined in the dependent claims.

Thus, this invention is concerned with exploiting
5 the good surface finish, tight dimensional tolerance and three dimensional magnetic flux carrying capabilities of soft magnetic composites by breaking a motor's iron core into separate tooth and core back sections. These separate sections allow separately produced simple bobbin
10 wound type coils to be assembled with the core sections to make units which are joined together and assembled within the motor's frame.

The coils being produced away from the geometric difficulties of insertion into the slots can have a far
15 higher ratio of copper to slot area; using machine winding 70% is easily achieved. If the further step is taken to compress the coils in a die, 81% has been achieved which is getting close to the theoretical maximum (which is fixed by the need for insulation around
20 the conductors).

The result of this high ratio of conductor to slot area is a major reduction in coil resistance and hence in ohmic losses and a large increase in thermal conduction. The result is that at limit the motor will produce far
25 more output, lowering capital cost and offering efficiency, size and weight benefits.

At the same time, the sub-components proposed are easily produced by cheap and fully automated processes, and the requirements for mechanical strength, withstand
30 of electrical breakdown and dimensional tolerance are easily met. This is in contrast to a conventional machine whose winding either requires much handwork or expensive and difficult-to-set-up winding machines.

Brief description of the drawings

35 FIG. 1 is a perspective view showing a separate tooth and a separate core-back section according to a

first embodiment of the present invention as well as a separate coil.

FIG. 2 is a plan view of the separate core-back section shown in FIG. 1.

5 FIG. 3 is a side view of the separate tooth shown in FIG. 1.

FIG. 4 is an end view of the separate tooth shown in FIGS. 1 and 3.

10 FIG. 5 is a side view corresponding to FIG. 3 and illustrating the components of FIG. 1 in an assembled state.

FIG. 6 is a cross-sectional view along the line VI-VI in FIG. 5.

15 FIG. 7 is a perspective view showing a separate tooth and a separate core-back section according to a second embodiment of the present invention.

FIG. 8 is a perspective view showing the components of FIG. 7 in an assembled state.

Description of the preferred embodiment

20 A stator tooth 1 illustrated in FIGS. 1 and 3-6 has a stem 2 of constant cross-sectional area and a distal tip 3 of larger cross-sectional area than the stem 2. Preferably, the tooth 1 is made by compressing a soft magnetic powder material, such as Somaloy 500 made by
25 Höganas AB of Sweden.

The stator tooth 1 has a proximal end portion 4 of the same cross-sectional area as (or less cross-sectional area than) the stem 2.

30 A stator core-back section 5 illustrated in FIGS. 1, 2, 5 and 6 is of conventional shape except for a radial through-hole 6 having the same cross-sectional area as the proximal end portion 4 of the tooth 1 in FIGS. 1 and 3-6. The core-back section 5 may be made of the same material as the tooth 1, the surface of the hole 6 as
35 well as the dimensions thereof being such as to enable a close fit with the proximal end portion 4 of the tooth 1.

FIGS. 1, 5 and 6 also illustrates a coil 7 to be assembled with the tooth 1 and the core-back section 5 to form a stator section, as shown assembled in FIGS. 5 and 6. Further, nine such stator sections may be assembled to form a complete stator core but the number of sections used may be varied by appropriately changing the dimensions and angles of each tooth 1 and core-back section 5.

In assembling a single stator section, the coil 7 is first slid on to the stem 2 of the tooth 1 from the proximal end portion 4 towards the distal tip 3. In order that this should be possible without any substantial gap existing between the coil 7 and the tooth 1 in the assembled state, stem 2 should have non-decreasing cross-sectional dimensions, i.e. substantially constant or increasing cross-sectional dimensions, from the proximal end portion 4 to the distal tip 3, i.e. along a length of the tooth corresponding to a winding slot. Also, the shape of the central hole of the coil 7 should correspond to the shape of the stem 2.

The second embodiment of a stator core illustrated in FIGS. 7 and 8 comprises a tooth 11 having a stem 12, a distal tooth tip 13, and a proximal end portion 14. Further, this stator core has a core-back section 15 split into two symmetrical halves 15' and 15" which when assembled as shown in FIG. 8 has a hole 16', 16" having the same shape as the proximal end portion 14 of the tooth 11. As a consequence of the split core-back section 15, the hole 16', 16" and the proximal end portion 14 may have such a shape that the tooth 11 is fixed between the two halves 15' and 15" in the assembled state of the stator core section.

To form a complete stator core the components shown in FIGS. 7 and 8 are doubled and assembled with a coil on each one of the two the opposing teeth.

While two embodiments of the present invention are described above, it is obvious to the man skilled in the

art that several modifications are possible without departing from the spirit of the present invention.

Thus, the core-back sections 5 of the first embodiment may be split in the same way as the core-back sections 15 of the second embodiment. Further, each one of these halves may be integrated with the nearest half of an adjoining core-back section 5, such that each core-back section includes a half of each of two openings.

CLAIMS

1. A stator core for an electrical machine,
comprising
 - 5 an annular yoke and plurality of teeth spaced circumferentially on the annular yoke and extending radially therefrom, the spaces between the teeth defining circumferentially spaced winding slots,
characterised in
 - 10 that the teeth are formed as separate components from a soft magnetic powder material, each tooth (1; 11) having non-decreasing cross-sectional dimensions in a direction towards a distal tip (3; 13) along a length of the tooth corresponding to a winding slot, and having the
 - 15 same or smaller cross-sectional dimensions along a proximal end (4; 14) of the tooth to be assembled with a section (5; 15) of the annular yoke and to be able to receive a coil (7) before the assembling with the yoke.
 2. A stator core for an electrical machine as
 - 20 claimed in claim 1, wherein openings (6; 16', 16'') are provided in the annular yoke, each opening receiving the proximal end (4; 14) of one tooth (1; 11).
 3. A stator core for an electrical machine as
claimed in claim 2, wherein the yoke comprises as many
 - 25 core-back sections (5; 15) as there are teeth (1; 11).
 4. A stator core for an electrical machine as
claimed in claim 3, wherein each core-back section (5;
15) includes an opening (6; 16', 16'').
 5. A stator core for an electrical machine as
 - 30 claimed in claim 4, wherein each core-back section (15) is split in two halves (15', 15'') each half including half the opening (16', 16'').
 6. A stator core for an electrical machine as
claimed in claim 3, wherein each core-back section
 - 35 includes a half of each of two openings.
 7. A stator assembly for an electrical machine,
comprising a stator core as claimed in any one of claims

1-6, and further comprising coils wound directly on the teeth before the assembling thereof with the yoke.

8. A stator assembly for an electrical machine, comprising a stator core as claimed in any one of claims 1-6, and separately wound bobbin coils (7) inserted on the teeth (1) before the assembling thereof with the yoke.

1/4




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00923

A. CLASSIFICATION OF SUBJECT MATTER		
IPC7: H02K 1/14, H02K 1/18 // H02K 15/06 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
IPC7: H02K		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
SE,DK,FI,NO classes as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 2134039 (F. GEHRIG & CO. AG), 25 January 1973 (25.01.73), page 3, line 7 - page 5, line 9, figure 1 --	1-8
A	US 5729072 A (MIKO HIRANO ET AL), 17 March 1998 (17.03.98), figures 1-2, abstract --	1-8
P,A	WO 9950949 A1 (HÖGANÄS AB), 7 October 1999 (07.10.99), abstract --	1-8
P,A	WO 9954985 A1 (HÖGANÄS AB), 28 October 1999 (28.10.99), abstract -- -----	1-8
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
15 August 2000		28 -08- 2000
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86		Authorized officer Tomas Erlandsson/mj Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/SE 00/00923

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
DE	2134039		25/01/73	NONE	
US	5729072	A	17/03/98	JP 6105487 A	15/04/94
WO	9950949	A1	07/10/99	AU 7946998 A SE 9801123 A	30/12/98 01/10/99
WO	9954985	A1	28/10/99	SE 9801401 D	00/00/00